



PRODUCT DATA SHEET LUBRICANTS

VP ENGINE ASSEMBLY LUBE

VP Engine Assembly Lube is formulated to cling to engine parts and designed for use by technicians and mechanics during engine building.

VP Engine Assembly Lube will mix with other oils unlike grease based assembly lubes preventing clogging of ports/filters on initial engine start up.

VP Engine Assembly Lube contains ZincDialkyIDithioPhosphate (ZDDP) and Molybdenum compounds providing rust/corrosion protection and perfect for long time storage of parts.

TYPICAL PROPERTIES

Engine Assembly Lube		
Product Number	2251 (12 Ounce Bottle)	Test Method
Viscosity@40°C, cSt	486	ASTM D445
Viscosity@100°C, cSt	58.2	ASTM D7042
Viscosity Index (VI)	190	Calculated
Specific Gravity @ 60°F	0.87	Calculated
API Gravity	30.4	Calculated
Flash Point, °C	>220	ASTM D92
Pour Point, °C	<-15	ASTM D97

These properties are typical of the current production. Variations that do not affect product performance are to be expected depending on blending and manufacturing locations. The information above is subject to change without notice.

Health and Safety:

This product is unlikely to have any adverse health implications or safety hazards when used for its intended application. Avoid contact with skin, use resistant gloves when handling used oil. If skin comes in contact wash immediately with soap and water. For complete information on safe handling and product characteristics please refer to the Safety Data Sheet (SDS).